

CO-7032 N-XM

32 Channels 1080N HD DVR



Features:

- 32 CH video input
- H.264 dual-stream video compression
- Support VGA, HDMI full HD output simultaneously;
- support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, CMS, center platform management software XM eye
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, etc.)

Technical Specifications

Model	CO-7032N-XM(1080N AHD DVR)	
Interface	Operating interface	support 16-bit true color graphical menu interface and mouse operation
	Preview	1/4/9/16/32
Video	Codec	H.264
	Monitor quality	VGA、 HDMI : HD
	Encode ability	32*AHD-H (1080N)
	Decode ability	8*AHD-H (1080N)
	Multi-mode input	analog: 32*AHD-H; (1080N), Network : 8*1080 & 8*1080N, 8*5M;
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	8ch(local input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	32ch BNC

	Video output	1ch VGA,1ch HDMI
	Audio input	16ch RCA
	Audio output	1ch RCA
	Network interface	RJ45 10M/100M
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2*USB 2.0 ports
	HDD	2*SATA ports (Max 6TB)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V-5A/6A
	Power Consumption	<45W (without HDD)
	Working environment	Temperature:0°C—+55°C, Humidity:10%—90%, Atm:86kpa—106kpa